

# EFD

## Inhibitor 300765

- Aid to the extension of the working time with 2K-Polyurethane systems

<b>Technical / Physical Data</b>	<b>Resin/ binder</b>	organic acid
	<b>Colour</b>	easily yellowish
	<b>Density</b> calculated	0,95 g / ml + / - 0,01
	<b>Solid content</b> calculated	approx. 5 %
<b>Storability</b>	Approx. 12 month in original packings at an ambient temperature of 15 to 25 °C, in case the original packings are tightly closed. Opened packing must be used very shortly. The minimum storage stability of each batch is mentioned on the product label. A storage time beyond the mentioned date doesn't necessarily mean that the material is unusable. In this case a check of the qualities which are important for the respective	
<b>Processing and application</b>	<b>Application</b>	addition quantity: approx 0,5 to 2,0% by weight, calculated after hardener addition
	<b>Application temperature</b>	above 10 °C
	<b>Advise for safety protection and protection of health</b>	The usual precautionary measures for ventilation as well as for personal protection are to be observed when handling painting materials. Detailed information about dangerous goods, sayfety data and recommendations concerning health protection and environment protection can be read in the corresponding safety data sheet.
<b>Special remarks</b>	<b>Test condition</b>	All information are based on our product knowledge and experience. To the application we have no direct influence. For further information please don't hesitate to contact us.  The information mentioned herein are reference values and are not given as specification.